

NEGATIVE FRESNEL LENSES

Part Number	Focal Length	Facet Spacing	Fresnel Conjugate	Plano Conjugate	Clear Aperture	Thickness
SC 259 neg.	-18.3 mm	0.254 mm	infinity	-18.3 mm	16.6 mm	1.8 mm
SC 239 neg.	-102.8 mm	0.508 mm	infinity	-102.8 mm	139.4 mm	1.8 mm
SC 902 neg.	-129.6 mm	0.254 mm	infinity	-129.6 mm	230.1 mm	1.8 mm
DC 1100L neg.	-185.8 mm	0.508 mm	infinity	-185.8 mm	269.0 mm	1.8 mm
DC 427L neg.	-205.7 mm	0.508 mm	infinity	-205.7 mm	302.0 mm	1.8 mm
DC 434U neg.	-255.3 mm	0.508 mm	infinity	-255.3 mm	302.0 mm	1.8 mm
SC 973 neg.	-508.0 mm	0.508 mm	infinity	-508.0 mm	408.7 mm	1.8 mm
SC 2135 neg.	-764.0 mm	0.508 mm	infinity	-764.0 mm	436.3 mm	1.8 mm

Notes:

- Focal lengths listed apply to 546 nm for PMMA (tolerance $\pm 5\%$).
- The standard material used is PMMA (refractive index = 1.49; relative dispersion = 58). Other materials are available.
- The mentioned thickness value is our standard thickness. Other thicknesses (≥ 0.8 mm) are possible.
- Outside diameter / size may be up to 5 – 20 mm beyond clear aperture. Other dimensions or special trimmings can be realized upon request.
- To determine the number of lines per mm, use $1/\text{facet spacing}$.
- Special designs possible on request.
- All specifications are subject to change without prior notice.

Engineered to Manage Light™

ORAFOL Fresnel Optics GmbH

Flurstedter Marktweg 13 • 99510 Apolda • Germany

Tel.: +49 3644 5011 0 • Fax: +49 3644 501150

E-Mail: sales@fresnel-optics.de • www.fresnel-optics.de

